

# TOTAL SCHEEPVAART GASOLIE FLASH 60

## Productspecification



### Marine Fuel

	Method	Unit	Minimum	Typical	Maximum
<b>Appearance (20°C)</b>	Visual	-	<i>Clear and bright</i>		
<b>Color</b>	Visual	-		Red	
<b>Solvent Yellow 124</b>		mg/l	6,0		9,0
<b>Density (15°C)</b>	EN 12185	kg/m <sup>3</sup>	820		860
<b>Viscosity (20°C)</b>	ISO 3104	kg/m <sup>3</sup>	-		6,0
<b>Flashpoint (Pensky Martens)</b>	EN ISO 2719	°C	Above 60		-
<b>Ash</b>	ISO 6245	% m/m	-		0,01
<b>Micro Carbon Residue</b> After 10% distillation	ISO 10370	% m/m	-		0,30
<b>Total Acid Number</b>	ASTM D 974	mgKOH/g			0,50
<b>Cloudpoint</b>	EN ISO 3015	°C			+3
<b>CFPP (Cold Filter Plugging Point)</b>	EN 116				
At Cloudpoint +1°C		°C	-		- 10
At Cloudpoint +2°C		°C	-		- 11
At Cloudpoint +3°C		°C	-		- 12
<b>Sulphur Content</b>	EN ISO 24260	mg/kg			1000
<b>Cetane index</b>	EN ISO 4264	-	45		
<b>Water content</b>	EN ISO 12937	mg/kg	-		200
<b>Distillation:</b>	EN ISO 3405				
▶ Volume recovered at 250 °C		% (v/v)	-		65
▶ Volume recovered at 350 °C		% (v/v)	85		-
<b>Total Contamination</b>	EN 12662	mg/kg	-		24

TOTAL Nederland N.V.  
Nieuwe Havenstraat 2  
2272 AD Voorburg